

Model 7500 Series

Tabletop Pulse Oximeter



Easy to use. Economical. Reliable performance.

Nonin's 7500 pulse oximeter has a unique low-profile design that enables it to fit easily on a tabletop or into its own carrying case. The stylish, compact 7500's simple functionality, minimum 16-hour battery life, 4-hour quick recharge, and minimum of 70 hours of memory makes it well-suited for a variety of clinical and homecare applications. Like all Nonin portable oximeters, the 7500 provides a wide range of display indicators that provide reliable readings.

The 7500's flexible alarm management options include patient security mode and a user-defined default that offers customizable patient settings. The 7500's analog output capability allows it to interface easily with other equipment.

A variety of single-use and reusable sensors are available for use with the Model 7500. Nonin Medical's PureLight® sensors produce accurate and dependable SpO₂ readings from patient-to-patient and sensor-to-sensor. Use only Nonin branded sensors.

Model 7500 Series

Product Highlights

- **Convenient** – Lightweight, compact
- **Easy-To-Use** – Bright LED displays and large display screen offer clear readability
- **Durable** – Rugged design
- **Powerful** – Over 70 hours of memory available for extended monitoring
- **Versatile** – Monitors neonate to adult patients in acute care to homecare environments
- **Flexible** – Use as a stand alone device or interface with other equipment


Magnetic Resonance (MR) Model 7500 FO


The 7500FO (fiberoptic) pulse oximeter was specifically developed for MR environments. Use in fixed-site or mobile MR facilities for monitoring infant, pediatric and adult patients.




User-Friendly Interface

The 7500 provides a variety of display indicators that ensure reliable readings.

 **Pulse Strength Bar Graph** – Color coded bar graph assists in assessing the patient’s status. An audible tone sounds with each pulse. The pitch changes with the patient’s saturation level.

 **Pulse Quality Indicator** – Detects patient movement or signal quality changes that may require sensor site stabilization.

 **Sensor Fault Indicator** – Indicates when a sensor has become disconnected, misaligned, failed, or is incompatible with the monitor.

Specifications

Oxygen Saturation Display Range 0–100% SpO₂

Pulse Rate Range 18–321 BPM

Displays

Pulse Strength LED, Bar graph, tri-color segments

Alarm Indicator LED, bi-color

Alarm Silenced LED, amber

Numeric Displays 3-digit, 7-segment LEDs, green

Low Battery LED, amber

Saturation Accuracy (A_{rms})^a 70–100%

Adults/Pediatrics Neonates

No Motion: Reusable Finger Clip ± 2 digits ± 3 digits

Disposable 6000 Series ± 2 digits ± 3 digits

Motion: Reusable Finger Clip ± 2 digits NA

Pulse Rate Accuracy

No Motion: 18–300 BPM

Motion: 40–240 BPM

Low Perfusion: 40–240 BPM

Adults/Pediatrics Neonates

No Motion: Reusable Finger Clip ± 3 digits ± 3 digits

Disposable 6000 Series ± 3 digits ± 3 digits

Motion: Reusable Finger Clip ± 5 digits ± 5 digits

Low Perfusion: Reusable Finger Clip ± 3 digits ± 3 digits

Disposable 6000 Series ± 3 digits ± 3 digits

Memory 70 hours (assuming continuous operation)

Temperature (Operating) 0° to +40°C (32°F to 104°F)

(Storage/Transportation) -30° C to +50°C (-22°F to 122°F)

Humidity (Operating) 10–90% noncondensing

(Storage/Transportation) 10–95% noncondensing

Altitude (Operating) Up to 12,000 meters (40,000 feet)

Hyperbaric Pressure Up to 4 atmospheres

Power Requirements (Mains) 100–240 VAC 50–60 Hz

Internal Power

Battery 7.2 volt NiMH battery pack

Operating Life (fully charged battery) 16 hours minimum

Storage Life 21 days minimum

Recharge Rate 4 hours maximum

Dimensions Approximately 219 mm (8.6") W x

92 mm (3.6") H x 142 mm (5.6") D

Weight Approximately 900 grams (2 lbs) with battery

Warranty 3 years

Classification per IEC 60601-1/CSA601.1/UL60601-1

Type of Protection Class II (when on AC power with MPP30 battery charger), Internally powered (on battery power)

Degree of Protection Type BF-Applied Part

Mode of Operation Continuous

Enclosure Degree of Ingress Protection IPX2

Analog Outputs

SpO₂ Output Range 0-1 VDC (0–100% SpO₂), 1.27 VDC (out of track)

Pulse Rate Output Range 0-1 VDC (0–300 BPM), 1.27 VDC (out of track)

Event Marker 0 V (no event), 1 V (event occurred)

Accuracy ± 2% (SpO₂), ± 5% (Pulse Rate)


Load Current 2 mA maximum

Specifications are subject to change without notice.

^a ± 1 A_{rms} represents approximately 68% of measurements

Quality systems certified to ISO 13485, and CE per Annex II of EC Directive No. 93/42/EEC as amended by 2007/47/EC.

Authorized Distributor:



Nonin Medical, Inc.

13700 1st Avenue North

Plymouth, MN • 55441-5443 • U.S.A.

Tel: +1.763.553.9968 1.800.356.8874

Fax: +1.763.577.5521

E-mail: info@nonin.com

Nonin Medical B.V.

Prins Hendriklaan 26

1075 BD Amsterdam • Netherlands

Tel: +31 (0)13-79 99 040

Fax: +31 (0)13-79 99 042

E-mail: infointl@nonin.com

nonin.com

